



SCAN ME
Terms and
Conditions



SCAN ME
Website



SCAN ME
Catalogue

X-RAIL DATA SHEET



X-RAIL Horizontal Rigid Rail System


Overhead Concealed Fix (BeamLink)






The SafetyLink Concealed Fix X-Rail is a Rigid Anchor Line suitable for use as part of a personal fall protection system. The X-Rail offers a Horizontal Rigid Anchor Line with one or multiple mobile anchor points for attaching to. The X-Rail can be used for Fall Arrest and Abseiling purposes.

- Overhead Mounted system for use on **Flanged Beams and Columns**.
- X-Rail is suitable when fall clearance is limited.
- Low profile rail and brackets, with hidden fasteners.
- The X-Rail Horizontal Rigid Rail System is rated for up to 4 users per system in any span.
- The X-Rail Horizontal Rigid Rail System is compliant with AS/NZS 1891.2, EN795:2012 and PD CEN/TS 16415:2013.

SHUTTLES

Product Code	Description	Material	
XRAIL-TR-011	X-Rail Shuttle Weight: 0.770kg	Aluminium	

TOOLS

XRAIL-TR-401	X-Rail Drill Bit to suit TR-101, TR102 Weight: 0.130kg	Steel	
XRAIL-TR-402	X-Rail Onsite Drill Fixture Weight: 0.492kg	Aluminium & Steel	
XRAIL-WARN	X-Rail Warning Sign Weight: 0.180kg	Stainless Steel	 <p>X-RAIL HORIZONTAL RIGID ANCHOR LINE</p> <p>NUMBER OF USERS: <input type="checkbox"/> 1x <input type="checkbox"/> 2x <input type="checkbox"/> 3x <input type="checkbox"/> 4x</p> <p>SYSTEM USE: <input type="checkbox"/> Fall Arrest <input type="checkbox"/> Abseil</p> <p>INSTALLED DATE: / /</p> <p>STANDARDS: EN795:2012, CSAS 1891.2:2013, AS/NZS 1891.2:2009</p> <p>ONLY EVER CONNECT 1 USER TO EACH SHUTTLE</p> <p>1x</p> <p>SAFETYLINK PTY LTD 401/402/403/404/405/406/407/408/409/410/411/412/413/414/415/416/417/418/419/420/421/422/423/424/425/426/427/428/429/430/431/432/433/434/435/436/437/438/439/440/441/442/443/444/445/446/447/448/449/450/451/452/453/454/455/456/457/458/459/460/461/462/463/464/465/466/467/468/469/470/471/472/473/474/475/476/477/478/479/480/481/482/483/484/485/486/487/488/489/490/491/492/493/494/495/496/497/498/499/500/501/502/503/504/505/506/507/508/509/510/511/512/513/514/515/516/517/518/519/520/521/522/523/524/525/526/527/528/529/530/531/532/533/534/535/536/537/538/539/540/541/542/543/544/545/546/547/548/549/550/551/552/553/554/555/556/557/558/559/560/561/562/563/564/565/566/567/568/569/570/571/572/573/574/575/576/577/578/579/580/581/582/583/584/585/586/587/588/589/590/591/592/593/594/595/596/597/598/599/600/601/602/603/604/605/606/607/608/609/610/611/612/613/614/615/616/617/618/619/620/621/622/623/624/625/626/627/628/629/630/631/632/633/634/635/636/637/638/639/640/641/642/643/644/645/646/647/648/649/650/651/652/653/654/655/656/657/658/659/660/661/662/663/664/665/666/667/668/669/670/671/672/673/674/675/676/677/678/679/680/681/682/683/684/685/686/687/688/689/690/691/692/693/694/695/696/697/698/699/700/701/702/703/704/705/706/707/708/709/710/711/712/713/714/715/716/717/718/719/720/721/722/723/724/725/726/727/728/729/730/731/732/733/734/735/736/737/738/739/740/741/742/743/744/745/746/747/748/749/750/751/752/753/754/755/756/757/758/759/760/761/762/763/764/765/766/767/768/769/770/771/772/773/774/775/776/777/778/779/780/781/782/783/784/785/786/787/788/789/790/791/792/793/794/795/796/797/798/799/800/801/802/803/804/805/806/807/808/809/810/811/812/813/814/815/816/817/818/819/820/821/822/823/824/825/826/827/828/829/830/831/832/833/834/835/836/837/838/839/840/841/842/843/844/845/846/847/848/849/850/851/852/853/854/855/856/857/858/859/860/861/862/863/864/865/866/867/868/869/870/871/872/873/874/875/876/877/878/879/880/881/882/883/884/885/886/887/888/889/890/891/892/893/894/895/896/897/898/899/900/901/902/903/904/905/906/907/908/909/910/911/912/913/914/915/916/917/918/919/920/921/922/923/924/925/926/927/928/929/930/931/932/933/934/935/936/937/938/939/940/941/942/943/944/945/946/947/948/949/950/951/952/953/954/955/956/957/958/959/960/961/962/963/964/965/966/967/968/969/970/971/972/973/974/975/976/977/978/979/980/981/982/983/984/985/986/987/988/989/990/991/992/993/994/995/996/997/998/999/1000</p>

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1334 Version: 3.0

Asia-Pacific/The Americas
info@safetylink.com

Europe/Africa/Middle East
europe.sales@safetylink.com

Northern Europe
uk.sales@safetylink.com



SCAN ME
Terms and
Conditions



SCAN ME
Website




SCAN ME
Catalogue

X-RAIL DATA SHEET



FS 707792

CONCEALED FIX X-RAIL

Product Code	Description	Material	
XRAIL-TR-101-2M XRAIL-TR-101-3M XRAIL-TR-101-5M XRAIL-TR-101-6M	Standard Rail: 2 metres - Weight: 3.958kg Standard Rail: 3 metres - Weight: 5.937kg Standard Rail: 5 metres - Weight: 9.890kg Standard Rail: 6 metres - Weight: 11.874kg	Aluminium	
End & Intermediate Anchor + Beam Fixings (Concealed Fix): XRAIL-TR-201+ BEAM_FIXINGS	1 x XRAIL-TR-201: End & Intermediate Anchor 1 x Socket Head Countersunk Screw M12x45mm 1 x Washer: M12 1 x Spring Washer: M12 1 x Nut: M12 Weight: 0.183kg	Aluminium & 316SS	 **
Rail Join Kit: joins straight rail lengths. XRAIL-TR-002	1 x XRAIL-TR-206: Rail Join 4 x XRAIL-TR-907(OTS): M10 x 40 Countersunk Cap Screw 1 x XRAIL-TR-212: Rail Dowel Weight: 0.405kg	Aluminium & 316SS	
End Kit + Beam Fixings (Concealed Fix): XRAIL-TR-041+ BEAM_FIXINGS	1 x XRAIL-TR-201+Beam_Fixings: End & Intermediate Anchor 1 x XRAIL-TR-006: Shuttle Stop 1 x XRAIL-TR-008: System Termination Kit 1 x XRAIL-TR-213: Rail End Cap Weight: 0.430kg	Aluminium & 316SS	 **
BeamLink 160mm: Install to structural flanged beam size upto 160mm BEAMLINK001.160	1 x Nut: M24 1 x Washer: M24 1 x BeamLink Clamp End 1 x Washer: M12 Shoulder 1 x Threaded Rod: M24 x 370mm Weight: 5.736kg	Galvanised & Nylon Washer	
BeamLink 210mm: Install to structural flanged beam size upto 210mm BEAMLINK001.210	1 x Nut: M24 1 x Washer: M24 1 x BeamLink Clamp End 1 x Washer: M12 Shoulder 1 x Threaded Rod: M24 x 42mm Weight: 5.884kg	Galvanised & Nylon Washer	
BeamLink 285mm: Install to structural flanged beam size upto 285mm BEAMLINK001.285	1 x Nut: M24 1 x Washer: M24 1 x BeamLink Clamp End 1 x Washer: M12 Shoulder 1 x Threaded Rod: M24 x 50mm Weight: 6.122kg	Galvanised & Nylon Washer	
BeamLink 385mm: Install to structural flanged beam size upto 385mm BEAMLINK001.385	1 x Nut: M24 1 x Washer: M24 1 x BeamLink Clamp End 1 x Washer: M12 Shoulder 1 x Threaded Rod: M24 x 60mm Weight: 6.418kg	Galvanised & Nylon Washer	

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1334 Version: 3.0

Asia-Pacific/The Americas
info@safetylink.com

Europe/Africa/Middle East
europe.sales@safetylink.com

Northern Europe
uk.sales@safetylink.com