



- ▲ Base Platform must be level within 3 degrees,
- ▲ Required if entry/exit area not level.
- ▲ Step down to roof/ground must not exceed 300mm.
- ▲ Suitable for roof pitches 0 to 15 degrees only.
- ▲ Adjustable.
- ▲ FastFit ladder system is designed for single person use and rated for maximum 150kg.
- ▲ FastFit ladders are manufactured to AS 1657:2018 Standards.

COMPLETE UNIT - PRODUCT CODE: LADER002.PLT.BASE		Weight: 12.6kg	
Components	Description	Material	Qty
LADER002.PLT.BASE.01	Base Platform Kit	Aluminium	1
SCREW 12-14x20mm	Screw: 12-14x20mm Self Tapping	Galvanised	12
SCREW 12-14x35mm	Screw: 12-14x35mm Self Tapping	Galvanised	2
AL_GRATING DISC	Washer: Grating Disc	Aluminium	2
BOLT-M8x60mm Cup HD	Bolt: M8x60mm Cup Head	316SS	2
NUT M8 Flanged_316	Flanged Nut: M8	316SS	2
RIVET_5x22mm	Rivet: 5 x 22mm	Aluminium	3
FOAM-TAPE-SQUARE	Foam Tape: 40 x 40 x 1.6mm	EPDM	3



SCAN ME
Manual



SCAN ME
Website



SCAN ME
Catalogue



SCAN ME
Safety Centre
Training

Ladder Examples



Kit: LADERK002.012+BASE



Kit: LADERK002.022+BASE

A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-899 Version: 7.0