



- ▲ Footing Platform must be level within 3 degrees.
- ▲ Step down to ground must not exceed 300mm.
- ▲ Platforms required if exit/entry not level.
- ▲ FastFit ladder system is designed for single person use and rated for maximum 150kg.
- ▲ FastFit ladders are manufactured to AS 1657:2018 Standards.

### COMPLETE UNIT - PRODUCT CODE: LADER002.PLT.FOOT

Weight: 9.6kg

Components	Description	Material	Qty
LADER002.PLT.FOOT.01	Footing Platform Kit	Aluminium	1
SCREW 12-14x20mm	Screw: 12-14x20mm Self Tapping	Galvanised	4
SCREW 12-14x35mm	Screw: 12-14x35mm Self Tapping	Galvanised	6
RIVET_5x22mm	Rivet: 5 x 22mm	Aluminium	4
FOAM-TAPE-SQUARE	Foam Tape: 40 x 40 x 1.6mm	EPDM	4



SCAN ME  
Manual



SCAN ME  
Website



SCAN ME  
Catalogue



SCAN ME  
Safety Centre  
Training

### Ladder Examples



Kit: LADERK002.164+FOOTING PLATFORM



Kit: LADERK002.094+FOOTING PLATFORM

**A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT**

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@safetylink.com](mailto:ip@safetylink.com) and quote the product code.

Doc ID: MKT-900 Version: 8.0