









- ▲ Ladder cages are highly recommended for ladders over 3.5 metres.
- △ Ladder Cage Extension should be used at the bottom of a ladder where there is a fall risk.
- Heavy gauge aluminium for superior strength.
- ▲ FastFit ladder system is designed for single person use and rated for maximum 150kg.
- FastFit ladders are manufactured to AS 1657:2018 Standards.

COMPLETE UNIT - PRODUC	T CODE: LADER002.CAGE.EXTN		
Product Code	Description	Material	Qty
LADER002.CAGE.JOIN.01	Ladder Cage Join Plate	Aluminium	1
LADER002.CAGE.EXTN.01	Side Extension Ladder Hoops	Aluminium	2
CAGE.BARS.1000	1000mm Cage Bars	Aluminium	3
BOLT-M8x60mm Cup HD	Bolt: M8x60mm Cup HD	316SS	2
BOLT-M8x30mm Cup HD	Bolt: M8x30mm Cup HD	316SS	2
BOLT-M8x20mm Cup HD	Bolt: M8x20mm Cup HD	316SS	5



Manual



Website



Catalogue



Safety Centre Training

Ladder examples below



Kit: LADERK002.091

A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1070 Version: 2.0

