



SCAN ME

www.safetylink.com



SCAN ME

Catalogue



SCAN ME

Anchor Layout Video

DATA SHEET



PS 707792

CLASSIC SURFACELINK

Abseil Surface Mounted Anchor



- SurfaceLink **ABSEILING ANCHOR** for use on Klip-lok roof sheeting where access to the structure is difficult.
- Needs to be secured with 8x 8mm Rivets and 2x Hex Head Screws.
- The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

STANDARDS

Complies with AS/NZS 1891.4 and AS/NZS 5532-2013.

IMPORTANT NOTICE: Size 14.10x80mm All-Thread Hex Head Screws are supplied but if they don't penetrate the batten by a minimum of 35mm, longer screws need to be used.

COMPLETE UNIT - PRODUCT CODE: HSURFABK002+FIXINGS		Weight: 1.617kg	
Product Parts	Description	Qty	Material
EYEBOLT M16x26mm	Collared Eyebolt: M16x26mm	1	316 SS
ADV-PLATE-SS-305-K	Classic SurfaceLink Plate for Klip-lok	1	316 SS
WASHER 70od-SS	Washer: 70mm OD	2	316 SS
WASHER M16_SPRING	Spring Washer: M16 316SS	1	316 SS
NUT M16	Nut: M16 316 Stainless Steel	1	316 SS
FOAM-TAPE 29 cm	Adhesive single sided tape	2	Foam
Rivet_8mm(27.7)	Aluminium 8mm Tri-fold Rivets	8	Aluminium
SCREW 14.10x80mm	14.10x80mm All-Thread Hex Head Screw with seal – Metal Tip	2	Steel

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1109 Version: 6.0

Asia-Pacific/The Americas
info@safetylink.com

Europe/Africa/Middle East
europa.sales@safetylink.com

Northern Europe
uk.sales@safetylink.com