



# SafetyLink® XtraLight TempLink 5000 Roofers Kit

Product code: ROOFKIT\_SL+TEMPL5000

## SafetyLink's TempLink 5000 Roofers Kit components:

- 1 x SafetyLink XtraLight Harness with Suspension Trauma Relief Straps.
  - 1 x SafetyLink 20m Adjustable Rope Line with Energy Absorber and two Karabiners.
  - 1 x SafetyLink TempLink 5000 (Temporary Roof Anchor).
  - 1 x Anchor Strap.
  - 2 x SafetyLink Karabiners.
  - 1 x SafetyLink Gear Bag.
- ▲ SafetyLink's XtraLight harness is fitted with all alloy hardware to reduce weight on the user.
  - ▲ 5 point adjustable XtraLight harness which caters for a wider range of personnel.
  - ▲ XtraLight harness is equipped with dorsal extension strap for ease of connection to rear fall arrest point.
  - ▲ 20 metre rope line with lightweight rope grab and built in energy absorber to give you greater access.
  - ▲ Aluminium double action karabiners with 16kN gate strength to help eliminate forced rollout.
  - ▲ Heavy duty backpack with external clear window for inspection record card storage.
  - ▲ TEMPLINK 5000 is a patented multi-directional fall device designed to absorb energy when a fall is arrested.

SafetyLink Pty Ltd **1300 789 545**  
+61 2 4964 1068 info@safetylink.com



For further information please visit our website [www.SafetyLink.com](http://www.SafetyLink.com)

# SafetyLink TempLink Roofers Kit Components

## XtraLight Harness

HARNES017



- Lightweight.
- Front and Rear attachment points.
- Gear loops for rescue scenarios.
- Adjustable quality alloy buckles creating maximum user adjustment.
- Traceability label pack includes a page that can be easily marked with site specific traceability documentation.
- Suspension trauma relief straps.

## 20m Rope Line

ROPELN013



- 20 metre Rope Line (red and black).
- Light weight alloy Rope Grab.
- 140kg Shock Pack and Karabiner.

Standard  
20m  
Rope Line

## TempLink 5000

TEMPL005



- 316 stainless steel.
- Easy grip handle.
- Less fixings required due to energy absorbing features.
- Suitable for mounting on metal roof sheeting with steel purlins or timber battens.
- Single person temporary roof anchor.
- Rated at 15kN.
- Complies with AS/NZ5532:2013 and EN759:2012.

## Karabiner

KARBNR022



- High strength aluminium Karabiner.
- Minimum breaking strength Rated 23kN.
- Gate opening 17mm.
- Double action.
- 16kN Rated gate strength.

## Gear Bag

BAGSL01



- Heavy duty nylon.
- Easy fold down opening, convenient to carry.
- Top carry handle.
- External clear window for inspection record card storage.

## Anchor Strap

ASTRAP003



- 1.5 metre red 25mm Webbing Anchor Strap.
- Flat construction.
- Rated to 21kN.

SafetyLink Pty Ltd **1300 789 545**  
+61 2 4964 1068 info@safetylink.com



For further information please visit our website [www.SafetyLink.com](http://www.SafetyLink.com)