

# BeamLink Anchor



The BeamLink is designed to be mounted overhead on flanged beams like universal beams, columns and fabricated sections.

- BeamLink structural beam attachment anchor.
- When fitted with eyehook the product is compliant with AS/NZS 5532:2013.
- Rated 21kN.

All safety procedures must comply in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety system.



| COMPLETE UNIT - PRODUCT CODE: EYEHOOK M16_ANZ2+BEAM_FIXINGS |                           |          |     | 0.327       |
|-------------------------------------------------------------|---------------------------|----------|-----|-------------|
| Product Parts                                               | Description               | Material | Qty | Weight (kg) |
| EYEHOOK M16_ANZ2                                            | Eyehook M16 (no thread)   | 316SS    | 1   | 0.243       |
| FROGLINE BUSH M16-M12                                       | FrogLine Bush: M16 to M12 | 316SS    | 1   | 0.009       |
| BOLT-M12x45mm                                               | Bolt: M12x45mm            | 316SS    | 1   | 0.052       |
| WASHER M12_316                                              | Washer: M12               | 316SS    | 1   | 0.003       |
| WASHER M12_Spring_316                                       | Washer: M12 Spring        | 316SS    | 1   | 0.004       |
| NUT M12_316                                                 | Nut: M12                  | 316SS    | 1   | 0.016       |

**\*\*\* BEAMLINK SUPPLIED SEPARATELY, SEE PAGE 2 TO ADVISE LENGTH REQUIRED (160 / 210 / 285 / 385)**

PRODUCT CODE: BEAMLINK001.160

PRODUCT CODE: BEAMLINK001.210

PRODUCT CODE: BEAMLINK001.285

PRODUCT CODE: BEAMLINK001.385

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



Page 1 of 2

© 2018, SafetyLink Pty Ltd, Australia.

**Patents:** SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@safetylink.com](mailto:ip@safetylink.com) and quote the product code.

Doc ID: MKT-1325 Version: 4.0

Asia-Pacific/The Americas  
[info@safetylink.com](mailto:info@safetylink.com)

Europe/Africa/Middle East  
[europe.sales@safetylink.com](mailto:europe.sales@safetylink.com)

Northern Europe  
[uk.sales@safetylink.com](mailto:uk.sales@safetylink.com)



SCAN ME

[www.safetylink.com](http://www.safetylink.com)



SCAN ME

Terms and Conditions



SCAN ME

Catalogue

DATA SHEET



FS 707792



SCAN ME

www.safetylink.com



SCAN ME

Terms and Conditions



SCAN ME

Catalogue

# DATA SHEET



FS 707792

The BeamLink is designed to be mounted overhead on flanged beams like universal beams, columns and fabricated sections. Select the length required to add to Anchor components.



| PRODUCT CODE: BEAMLINK001.160 – TO FIT 160mm FLANGE |                      |            |      | 5.736       |
|-----------------------------------------------------|----------------------|------------|------|-------------|
| Product Parts                                       | Description          | Material   | Qty  | Weight (kg) |
| NUT M24_GAL                                         | Nut: M24             | Galvanised | 4    | 0.716       |
| WASHER M24_GAL                                      | Washer: M24          | Galvanised | 2    | 0.068       |
| BEAMLINK001.01                                      | BeamLink Clamp End   | Galvanised | 2    | 3.846       |
| WASHER M12_SHOULDER_NYLON                           | Washer: M12 Shoulder | Nylon      | 4    | 0.008       |
| ROD-per metre M24-GAL                               | Threaded Rod: M24    | Galvanised | 0.37 | 1.098       |



| PRODUCT CODE: BEAMLINK001.210 – TO FIT 210mm FLANGE |                      |            |      | 5.884       |
|-----------------------------------------------------|----------------------|------------|------|-------------|
| Product Parts                                       | Description          | Material   | Qty  | Weight (kg) |
| NUT M24_GAL                                         | Nut: M24             | Galvanised | 4    | 0.716       |
| WASHER M24_GAL                                      | Washer: M24          | Galvanised | 2    | 0.068       |
| BEAMLINK001.01                                      | BeamLink Clamp End   | Galvanised | 2    | 3.846       |
| WASHER M12_SHOULDER_NYLON                           | Washer: M12 Shoulder | Nylon      | 4    | 0.008       |
| ROD-per metre M24-GAL                               | Threaded Rod: M24    | Galvanised | 0.42 | 1.246       |



| PRODUCT CODE: BEAMLINK001.285 – TO FIT 285mm FLANGE |                      |            |      | 6.122       |
|-----------------------------------------------------|----------------------|------------|------|-------------|
| Product Parts                                       | Description          | Material   | Qty  | Weight (kg) |
| NUT M24_GAL                                         | Nut: M24             | Galvanised | 4    | 0.716       |
| WASHER M24_GAL                                      | Washer: M24          | Galvanised | 2    | 0.068       |
| BEAMLINK001.01                                      | BeamLink Clamp End   | Galvanised | 2    | 3.846       |
| WASHER M12_SHOULDER_NYLON                           | Washer: M12 Shoulder | Nylon      | 4    | 0.008       |
| ROD-per metre M24-GAL                               | Threaded Rod: M24    | Galvanised | 0.50 | 1.484       |



| PRODUCT CODE: BEAMLINK001.385 – TO FIT 385mm FLANGE |                      |            |      | 6.418       |
|-----------------------------------------------------|----------------------|------------|------|-------------|
| Product Parts                                       | Description          | Material   | Qty  | Weight (kg) |
| NUT M24_GAL                                         | Nut: M24             | Galvanised | 4    | 0.716       |
| WASHER M24_GAL                                      | Washer: M24          | Galvanised | 2    | 0.068       |
| BEAMLINK001.01                                      | BeamLink Clamp End   | Galvanised | 2    | 3.846       |
| WASHER M12_SHOULDER_NYLON                           | Washer: M12 Shoulder | Nylon      | 4    | 0.008       |
| ROD-per metre M24-GAL                               | Threaded Rod: M24    | Galvanised | 0.60 | 1.780       |