

BeamLink Anchor



The BeamLink is designed to be mounted overhead on flanged beams like universal beams, columns and fabricated sections.

- BeamLink structural beam attachment anchor.
- When fitted with eyehook the product is compliant with EN795 Type A:2012.
- Rated 12kN.

All safety procedures must comply in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety system.



PRODUCT CODE: EYEHOOK M16_EN+BEAM_FIXINGS

0.327

Product Parts	Description	Material	Qty	Weight (kg)
EYEHOOK M16_EN	Eyehook M16 (no thread)	316SS	1	0.243
FROGLINE BUSH M16-M12	FrogLine Bush: M16 to M12	316SS	1	0.009
BOLT-M12x45mm	Bolt: M12x45mm	316SS	1	0.052
WASHER M12_316	Washer: M12	316SS	1	0.003
WASHER M12_Spring_316	Washer: M12 Spring	316SS	1	0.004
NUT M12_316	Nut: M12	316SS	1	0.016

*** BEAMLINK SUPPLIED SEPARATELY, SEE PAGE 2 TO ADVISE LENGTH REQUIRED (160 / 210 / 285 / 385)

PRODUCT CODE: BEAMLINK001.160

PRODUCT CODE: BEAMLINK001.210

PRODUCT CODE: BEAMLINK001.285

PRODUCT CODE: BEAMLINK001.385

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



Page 1 of 2

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1327 Version: 4.0

Asia-Pacific/The Americas
info@safetylink.com

Europe/Africa/Middle East
europe.sales@safetylink.com

Northern Europe
uk.sales@safetylink.com



SCAN ME

www.safetylink.com



SCAN ME

Terms and Conditions



SCAN ME

Catalogue

DATA SHEET



FS 707792



SCAN ME

www.safetylink.com



SCAN ME

Terms and Conditions



SCAN ME

Catalogue

DATA SHEET



FS 707792

The BeamLink is designed to be mounted overhead on flanged beams like universal beams, columns and fabricated sections. Select the length required to add to Anchor components.



PRODUCT CODE: BEAMLINK001.160 – TO FIT 160mm FLANGE				5.736
Product Parts	Description	Material	Qty	Weight (kg)
NUT M24_GAL	Nut: M24	Galvanised	4	0.716
WASHER M24_GAL	Washer: M24	Galvanised	2	0.068
BEAMLINK001.01	BeamLink Clamp End	Galvanised	2	3.846
WASHER M12_SHOULDER_NYLON	Washer: M12 Shoulder	Nylon	4	0.008
ROD-per metre M24-GAL	Threaded Rod: M24	Galvanised	0.37	1.098



PRODUCT CODE: BEAMLINK001.210 – TO FIT 210mm FLANGE				5.884
Product Parts	Description	Material	Qty	Weight (kg)
NUT M24_GAL	Nut: M24	Galvanised	4	0.716
WASHER M24_GAL	Washer: M24	Galvanised	2	0.068
BEAMLINK001.01	BeamLink Clamp End	Galvanised	2	3.846
WASHER M12_SHOULDER_NYLON	Washer: M12 Shoulder	Nylon	4	0.008
ROD-per metre M24-GAL	Threaded Rod: M24	Galvanised	0.42	1.246



PRODUCT CODE: BEAMLINK001.285 – TO FIT 285mm FLANGE				6.122
Product Parts	Description	Material	Qty	Weight (kg)
NUT M24_GAL	Nut: M24	Galvanised	4	0.716
WASHER M24_GAL	Washer: M24	Galvanised	2	0.068
BEAMLINK001.01	BeamLink Clamp End	Galvanised	2	3.846
WASHER M12_SHOULDER_NYLON	Washer: M12 Shoulder	Nylon	4	0.008
ROD-per metre M24-GAL	Threaded Rod: M24	Galvanised	0.50	1.484



PRODUCT CODE: BEAMLINK001.385 – TO FIT 385mm FLANGE				6.418
Product Parts	Description	Material	Qty	Weight (kg)
NUT M24_GAL	Nut: M24	Galvanised	4	0.716
WASHER M24_GAL	Washer: M24	Galvanised	2	0.068
BEAMLINK001.01	BeamLink Clamp End	Galvanised	2	3.846
WASHER M12_SHOULDER_NYLON	Washer: M12 Shoulder	Nylon	4	0.008
ROD-per metre M24-GAL	Threaded Rod: M24	Galvanised	0.60	1.780