

## Delta Plus Single Lanyard (Elastic Webbing) with Energy Absorber

This Lanyard is suitable for use as a complete personal fall protection system. The Lanyard provides a connection between the users harness and an anchor. See AS/NZS 1891.4 for selection use and maintenance of suitable fall protection equipment.



### Standard

- ▲ Certified to AS1891.5:2020

### Material Specification

- ▲ Webbing & Thread: Polyester
- ▲ Hardware: High Tensile Steel, Zinc Plated
- ▲ Label: Vinyl
- ▲ Minimum User Capacity: 50kg
- ▲ Minimum Fall Clearance: 5.4m
- ▲ Maximum User Capacity: 150kg
- ▲ Minimum Fall Clearance: 6.6m
- ▲ Lifespan from manufacturing: 10 years
- ▲ Colour: Black/Orange



SCAN ME

www.safetylink.com



SCAN ME

Catalogue



SCAN ME

Safety Centre  
Training

Product Code	Harness Connector	Anchor Connector	Single or Twin	Leg Material	WEIGHT (KG)
WAUAN235200NN	Karabiner	Karabiner	Single	Elastic	0.80

**Always consult the instructions provided by the manufacturer of each component of your fall arrest system to accurately assess Fall Clearance.**

**Free-fall shall never exceed 2m.**

### Maintenance

The Lanyard shall be inspected before and after each use by the user. The Lanyard is not serviceable. Once the item fails inspection, is involved in a fall or if the remove from service date is reached (10 years from date of manufacturer for AS 1891.5 products) it shall be removed from service and destroyed to prevent use.

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@safetylink.com](mailto:ip@safetylink.com) and quote the product code.

Doc ID: MKT-7881 Version: 3.0